



Specification Data Sheet ICE BAN® 305

Product Description

Ice Ban® 305 is an all natural, unique and patented (U.S. Patent No. 5,635,101) anti-icing / deicing liquid chemical. It is a blend by volume of Ice Ban® and a 29% -31% Magnesium Chloride solution. Ice Ban® Ultra M is a **PNS Compliant** liquid that is non-toxic, bio-degradable and contains a naturally occurring corrosion inhibitor.

Compliance

Ice Ban® 305 is not approved for human consumption. It is intended for use as an anti-icing / deicing liquid chemical.

Applications

Ice Ban® 305 is intended for use as an ice and snow removal liquid chemical on highways and roads.

Caution: Extreme care and caution should be exercised when using Ice Ban® as an anti-icing chemical in advance of an approaching storm. The use and practice of applying anti-icing chemicals requires skill and specialized equipment. Liquid anti-icing chemicals can cause slickness if misused or over-applied. It is essential that conditions be evaluated individually to determine the most appropriate anti-icing program.

Packaging and Shipping

Ice Ban® 305 is available in bulk form only. Bulk quantities are shipped by truck or rail.

Storage and Handling

The storage of **Ice Ban® 305** requires the normal precautionary procedures used for the safe handling of liquids. Periodic re-circulation is suggested during long term storage. If mists are present during handling, safety glasses or goggles and rubber gloves should be used and skin contact areas should be thoroughly flushed with water.

Product Benefits

Ice Ban® 305 as tested in accordance with National Association of Corrosion Engineers (NACE) Standard TM-01-69 (1976 rev.), PNS modified exhibits corrosion values of at least 75% less than that of Sodium Chloride.

Ice Ban® 305 does not contribute to concrete scaling problems and has no adverse effect on the cohesive or adhesive strength of asphalt films.

Stock Pile and Pre-wetting Agent

Ice Ban® 305 is used as a stockpile treatment agent or pre-wetting agent at the rate of 8 gallons per ton of salt and 10-12 gallons per ton of abrasives.

Chemical Analysis

Component	Units	Typical	PNS Limit
MgCl ₂	%	25	25
Phosphorus	ppm	0.08	25
Cyanide	ppm	<0.05	0.2
Arsenic (As)	ppm	<1.0	5
Copper (Cu)	ppm	<0.1	0.2
Lead (Pb)	ppm	<0.50	1
Mercury (Hg)	ppm	<0.02	0.05
Chromium (Cr)	ppm	<0.50	0.5
Cadmium (Cd)	ppm	<0.05	0.2
Barium (Ba)	ppm	<0.50	10
Selenium (Se)	ppm	<1.0	5
Zinc (Zn)	ppm	0.61	10
pH (1:4 Solution)		7.0 - 8.0	6-10
Corrosion Rate	%	17.1	<30

Ref: ALI# 24283

Physical Properties

Component	Units	Typical
Specific Gravity	SGU (at 20°C)	1.276
TTL Settleable Solids (V/V)	%	≤1
Solids Passing #10 Sieve (V/V)	%	≥99
Freeze Point	-	-58° C / -67° F

Ref: ALI# 24283